

# K-FI PC-BEHAEL H ABLV MULTIFX MINI

Filters with polycarbonate bowl and semi-automatic drain valve

**HANSA FLEX**

## Características

|                                      |  |
|--------------------------------------|--|
| Presión de entrada                   | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| Temper. de medios                    | max. 60 °C   |
| Temp. entorno                        | Max. 60 °C   |
| Flujo de paso                        | 1000 l/min   |
| Ancho de poros en elemento filtrante | 5 µm   |
| Carcasa                              | Die-cast zinc  |
| Drain valve                          | Semi-automatic   |
| Medic. valor de flujo                | At P2 = 6 bar and pressure drop $\Delta p = 1$ bar         |



## Nota

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. Otras especificaciones a petición.

## Descripción

Centrifugal separators with a sintered filter element.

## Artículo

| Denominación   | Rosca | A (mm) | B        | C (mm) | D (mm) | DN | Tamaño constructivo |
|----------------|-------|--------|----------|--------|--------|----|---------------------|
| K- 07 25 00 42 | G 1/8 | 40,0   | 114,8 mm | 12,3   | 102,5  | 5  | 0                   |
| K- 07 25 00 44 | G 1/4 | 40,0   | 114,8 mm | 12,3   | 102,5  | 5  | 0                   |

## Piezas de repuesto

|                                |  |
|--------------------------------|--|
| K-AUTOMAT ABLASSVENTIL         | Automatic drain valve                        |
| K-KOPPELPAKET MEHR             | Coupling packet                              |
| K-ERSATZBEHAELTER MULTI MINI   | Spare tank »multifix-mini« & »standard-mini« |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter                    |
| K-FILTERELEMENT                | Filter element                               |