


# K-3/2-BKR MULTIFIX MINI

Ball valves

**HANSA FLEX**

## Características

Temper. de medios	max. 60 °C
Temp. entorno	Max. 60 °C
Accionam.	Twist knob, rotatable 90°
Flujo de paso	1800 l/min
Conex. de aireación	Silencer G 1/4
Material obturador	NBR
Carcasa	Die-cast zinc
Medic. valor de flujo	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Nota

If several devices in the »multiflex-mini« Series are assembled together, the maximum working pressure is 12 bar.  
Otras especificaciones a petición.

## Descripción

Rotary switch can be turned 90°, lockable, with relief port

## Artículo

Denominación	Rosca	A (mm)	B	C (mm)	D (mm)	Tamaño constructivo
K- 07 25 11 56	G 1/8	40,0	57,6 mm	37,6	20,0	0
K- 07 25 11 57	G 1/4	40,0	57,6 mm	37,6	20,0	0

## Piezas de repuesto

K-KOPPELPAKET MEHR	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted