

# K-NEBELOELER METALLBEHAE T STANDARD

Oil-mist lubricators with metal bowl and metal sight dome

**HANSA FLEX**

## Características

Presión de entrada	Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Temper. de medios	max. 60 °C
Temp. entorno	Max. 60 °C
Material obturador	NBR
Carcasa	Die-cast zinc, painted silver
Suplem. de goteo	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Tipo de aceite	CL 32 acc. to DIN 51517 - ISO VG 32
Medic. valor de flujo	At P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Otras especific.	User manual on request



## Descripción

Proportional lubricators, oil can be filled under pressure.

## Artículo

Denominación	Rosca	Flujo de paso (L/min)	A (mm)	C (mm)	D (mm)	DN
K- 07 25 08 88	G 1/4	1200	50,0	51,0	119,5	6
K- 07 25 08 91	G 3/8	1200	50,0	51,0	119,5	6
K- 07 25 08 94	G 3/8	2400	70,0	51,0	145,0	10
K- 07 25 08 97	G 1/2	4000	79,0	55,0	157,0	15
K- 07 25 09 00	G 3/4	9000	102,0	58,0	160,0	20
K- 07 25 09 03	G 1	9000	90,0	58,0	160,0	25
K- 07 25 09 06	G 1 1/4	9000	137,0	70,0	232,0	40
K- 07 25 09 09	G 1 1/2	9000	125,0	70,0	232,0	45

## Piezas de repuesto

K-HALTERBAUSATZ STANDARD	Holder
K-SCHUTZKORB G	Protective cage
K-TROPFAUFSATZ POLYCARBO	Drip attachment polycarbonate
K-XV AGM MS NI	Double nipples, parallel male thread, nickel-plated brass
K-RD NIPPEL MS NI	Reducing nipples - nickel-plated brass
K-LOESBARE DOPPELNIPPEL MS	Double nipples
K-TROPFAUFSATZ METALL	Drip attachment metal