

# K-DRG STANDARD-MINI

Pressure regulators

**HANSA FLEX**

## Características

|                       |  |
|-----------------------|--|
| Presión de entrada    | Max. 28 bar  |
| Temper. de medios     | max. 60 °C   |
| Temp. entorno         | Max. 60 °C   |
| Material obturador    | NBR/TPU  |
| Caperuza elást.       | POM-brass  |
| Carcasa               | Die-cast zinc, painted silver                                  |
| Medic. valor de flujo | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Otras especific.      | User manual on request   |



## Descripción

Reversible diaphragm pressure regulators with self-relieving design in compact design. The pressure setting can be locked by pushing the knob down.

## Artículo

| Denominación   | Rosca | Rango de regulación | Flujo de paso<br>(L/min) | A<br>(mm) | B       | C<br>(mm) | D<br>(mm) | DN |
|----------------|-------|---------------------|--------------------------|-----------|---------|-----------|-----------|----|
| K- 07 25 03 22 | G 1/8 | 0.15 - 3.5 bar      | 340                      | 43,0      | 72,5 mm | 9,5       | 63,0      | 5  |
| K- 07 25 03 23 | G 1/8 | 0.2 - 7.0 bar       | 340                      | 43,0      | 72,5 mm | 9,5       | 63,0      | 5  |
| K- 07 25 03 24 | G 1/8 | 0.5 - 10.0 bar      | 340                      | 43,0      | 72,5 mm | 9,5       | 63,0      | 5  |
| K- 07 25 03 25 | G 1/4 | 0.15 - 3.5 bar      | 340                      | 43,0      | 72,5 mm | 9,5       | 63,0      | 5  |
| K- 07 25 03 26 | G 1/4 | 0.2 - 7.0 bar       | 340                      | 43,0      | 72,5 mm | 9,5       | 63,0      | 5  |
| K- 07 25 03 27 | G 1/4 | 0.5 - 10.0 bar      | 340                      | 43,0      | 72,5 mm | 9,5       | 63,0      | 5  |

## Piezas de repuesto

|                            |   |
|----------------------------|---|
| K-HALTERBAUSATZ            | Holder  |
| K-SCHALTTAFELMUTTER        | Nut   |
| K-LOESBARE DOPPELNIPPEL MS | Double nipples  |
| K-XV AGM MS NI             | Double nipples, parallel male thread, nickel-plated brass |
| K-VERSCHLEI-SATZ           | Set of wearing parts                                      |