



K-WMAV 3/2 GEFUE ENTLUEF SCHL GEW

3/2-way solenoid valves, conveyed exhaust, pipe (input) - thread (output)

HANSA FLEX

Características

Presión de servicio	2.5 - 7 bar
Flujo 6,3bar, p=1bar	380 NI/min (Ø 6), 700 NI/min (Ø 8)
Potencia	1,2 W
Tensión	24 V DC
Rango de temperatura	-20 °C to +60 °C
Cuerpo	Technopolymer
Piezas int.	nickel-plated brass, brass, \ntechnopolymer, stainless steel
Material obturador	NBR
Montaje	Wall mounting (housing with drilled holes) Bracket mounting (mounting bracket available) Panel mounting (with bracket or lock nut)
Símbolo	on the housing



Nota

Otras especificaciones a petición.

Descripción

A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design. All components can be installed in parallel, in series, in a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection, with one plug connector and one nickel-plated brass thread.

Artículo

Denominación	Rosca	para Ø de manguera (mm)	Función	A (mm)	B (mm)	I (mm)
K- 07 15 14 03	G 1/8	6	NC	58,3	57,5	14,6
K- 07 15 14 04	G 1/8	8	NC	66,4	63,5	18,7
K- 07 15 14 01	G 1/4	6	NC	61,3	57,5	14,6
K- 07 15 14 02	G 1/4	8	NC	70,8	63,5	18,7
K- 07 15 14 05	G 3/8	8	NC	72,4	63,5	18,7
K- 07 15 14 08	G 1/8	6	NO	58,3	57,5	14,6
K- 07 15 14 09	G 1/8	8	NO	66,4	63,5	18,7
K- 07 15 14 06	G 1/4	6	NO	61,3	57,5	14,6
K- 07 15 14 07	G 1/4	8	NO	70,8	63,5	18,7
K- 07 15 14 10	G 3/8	8	NO	72,4	63,5	18,7