K-MAGV MINI

Miniature solenoid valves 15 mm

Características

Medios	Filtered, unlubricated compressed air
Rango de presión	0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override
Conexión	In manifold base
Rango de temperatura	-5 °C to +45 °C
Tiem. de apertura/cierre	10 - 12 ms (depending on pressure)
Potencia bobina	2,5 W
Material	Plástico
Material obturador	NBR, stainless steel



Nota

Otras especificaciones a petición.

Descripción

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Información adicional

Important: The scope of supply does not include a connector. Please order separately.

Artículo

Denominación	Función	Tensión	Conexión	H (mm)	B (mm)
K- 07 15 14 18	NC	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 19	NC	24 V DC	for system plug	42,0	15,0
K- 07 15 14 20	NC	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 21	NC	12 V DC	for system plug	42,0	15,0
K- 07 15 14 22	NO	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 23	NO	24 V DC	for system plug	42,0	15,0
K- 07 15 14 24	NO	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 25	NO	12 V DC	for system plug	42,0	15,0

Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.