

# K-PNEU LOGIKELEMENTE

Pneumatic logic elements

**HANSA FLEX**

## Características

Presión de funcionamiento	OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
Rango de temperatura	-10 °C to +60 °C
Conexión	Push-in fitting for 4 mm pipe
Flujo de paso	100 l/min (at 6 bar and $\Delta p = 1$ bar)
Ø nominal	2,7 mm
Reposición	OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
Material	Technopolymer
Corredera	Aluminium
Material obturador	NBR



## Nota

Otras especificaciones a petición.

## Descripción

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the  $\Omega$ -rail (DIN EN 50022) integral with the body.

## Artículo

Denominación	Función	Altura (mm)	Longitud (mm)
K- 07 15 13 77	OR	40	38,5
K- 07 15 13 78	AND	40	38,5
K- 07 15 13 79	NOT	40	55,2
K- 07 15 13 80	YES	40	55,2
K- 07 15 13 81	MEMORY	41	89,5