

K-WV 5/3 ELEKTROPNEU MITTELSTELLUNG

5/3-way pilot valves (monostable)

HANSA FLEX

Características

| | |
|-------------------------|--|
| Presión de servicio | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\nvacuum up to 10 bar (external pilot air) |
| Presión mín. de trabajo | 2.5 bar (monostable), 1.0 bar (bistable) |
| Rango de temperatura | -10 °C to +60 °C |
| Flujo 6bar y 10bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Flujo 6bar y 5bar | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |



Nota

Otras especificaciones a petición.

Artículo

| Denominación | Conexión | Tensión | DN | Función | Diagr. conexión no |
|----------------|----------|--------------|----|---------|--------------------|
| K- 07 15 03 30 | G 1/8 | 24 V DC | 5 | 5/3-way | 37 |
| K- 07 15 03 31 | G 1/4 | 24 V DC | 8 | 5/3-way | 37 |
| K- 07 15 25 87 | G 3/8 | 24 V DC | 13 | 5/3-way | 37 |
| K- 07 15 03 32 | G 1/2" | 24 V DC | 15 | 5/3-way | 37 |
| K- 07 15 03 33 | G 1/8 | 230 V, 50 Hz | 5 | 5/3-way | 37 |
| K- 07 15 03 34 | G 1/4 | 230 V, 50 Hz | 8 | 5/3-way | 37 |
| K- 07 15 25 88 | G 3/8 | 230 V, 50 Hz | 13 | 5/3-way | 37 |
| K- 07 15 03 35 | G 1/2" | 230 V, 50 Hz | 15 | 5/3-way | 37 |
| K- 07 15 03 36 | G 1/8 | 24 V DC | 5 | 5/3-way | 38 |
| K- 07 15 03 37 | G 1/4 | 24 V DC | 8 | 5/3-way | 38 |
| K- 07 15 25 89 | G 3/8 | 24 V DC | 13 | 5/3-way | 38 |
| K- 07 15 03 38 | G 1/2" | 24 V DC | 15 | 5/3-way | 38 |
| K- 07 15 03 39 | G 1/8 | 230 V, 50 Hz | 5 | 5/3-way | 38 |
| K- 07 15 03 40 | G 1/4 | 230 V, 50 Hz | 8 | 5/3-way | 38 |
| K- 07 15 25 90 | G 3/8 | 230 V, 50 Hz | 13 | 5/3-way | 38 |
| K- 07 15 03 41 | G 1/2" | 230 V, 50 Hz | 15 | 5/3-way | 38 |
| K- 07 15 03 42 | G 1/8 | 24 V DC | 5 | 5/3-way | 39 |
| K- 07 15 25 91 | G 3/8 | 24 V DC | 13 | 5/3-way | 39 |
| K- 07 15 03 43 | G 1/4 | 24 V DC | 8 | 5/3-way | 39 |
| K- 07 15 03 44 | G 1/2" | 24 V DC | 15 | 5/3-way | 39 |
| K- 07 15 03 45 | G 1/8 | 230 V, 50 Hz | 5 | 5/3-way | 39 |
| K- 07 15 03 46 | G 1/4 | 230 V, 50 Hz | 8 | 5/3-way | 39 |
| K- 07 15 25 92 | G 3/8 | 230 V, 50 Hz | 13 | 5/3-way | 39 |
| K- 07 15 03 47 | G 1/2" | 230 V, 50 Hz | 15 | 5/3-way | 39 |