

# K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

**HANSA FLEX**

## Características

<b>Presión de servicio</b>	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
<b>Rango de temperatura</b>	-10 °C to +60 °C
<b>Flujo 6bar y 10bar</b>	550 NI/min
<b>Flujo 6bar y 5bar</b>	400 NI/min
<b>Cuerpo de válv.</b>	Aluminio
<b>Muell</b>	Special steel
<b>Pistón</b>	Aluminium
<b>Material obturador</b>	NBR



## Nota

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Otras especificaciones a petición.

## Información adicional

Important: The scope of supply does not include a connector. Please order separately.

## Artículo

Denominación	Conexión	Símbolo	Accionam.	Pos. de conmutación
K- 07 15 00 82	G 1/8	9	monostable	2
K- 07 15 00 83	G 1/8	10	biestable	2
K- 07 15 00 84	G 1/8	11	monostable	3*
K- 07 15 00 85	G 1/8	12	biestable	3*