

K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

HANSA FLEX

Características

| | |
|-----------------------------|---|
| Presión de servicio | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Rango de temperatura | -10 °C to +60 °C |
| Flujo 6bar y 10bar | 550 NI/min |
| Flujo 6bar y 5bar | 400 NI/min |
| Cuerpo de válv. | Aluminio |
| Muell | Special steel |
| Pistón | Aluminium |
| Material obturador | NBR |



Nota

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Otras especificaciones a petición.

Información adicional

Important: The scope of supply does not include a connector. Please order separately.

Artículo

| Denominación | Conexión | Símbolo | Accionam. | Pos. de conmutación |
|----------------|----------|---------|------------|---------------------|
| K- 07 15 00 82 | G 1/8 | 9 | monostable | 2 |
| K- 07 15 00 83 | G 1/8 | 10 | biestable | 2 |
| K- 07 15 00 84 | G 1/8 | 11 | monostable | 3* |
| K- 07 15 00 85 | G 1/8 | 12 | biestable | 3* |