


# K-FI AK KOH PC-BEHÄEL S MULTIFIX

Activated carbon filters with polycarbonate bowl and bowl guard

## Características

Presión de entrada	Max. 16 bar
Temper. de medios	max. 60 °C
Temp. entorno	Max. 60 °C
Material obturador	NBR
Cartucho de filtro	Activated carbon-POM
Carcasa	Die-cast zinc
Drain valve	Semi-automatic
Contenido de aceite residual	0.005 mg/m <sup>3</sup>
Medic. valor de flujo	FA at P1 = 6 bar and $\Delta p = 0.2$ bar



## Nota

Otras especificaciones a petición.

## Descripción

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Artículo

Denominación	Rosca	Flujo de paso (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Tamaño constructivo
K- 07 25 10 50	G 1/4	380	47,8	136,8 mm	27,0	109,8	6	1
K- 07 25 10 53	G 1/2	1500	68,8	167,0 mm	34,5	132,5	15	2

## Piezas de repuesto

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-PC-BEHÄELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHÄELTER OELER MULTIFIX	Metal tank oiler