

# K-VORFI METALLBEHAEL MULTIFIX MINI

Pre-filters with metal bowl

**HANSA FLEX**

## Características

|                       |  |
|-----------------------|--|
| Presión de entrada    | Max. 16 bar  |
| Temper. de medios     | max. 60 °C   |
| Temp. entorno         | Max. 60 °C   |
| Finura del filtro     | 0,30 µm  |
| Efectividad           | 99.999 %   |
| Material obturador    | NBR  |
| Cartucho de filtro    | Paper-POM  |
| Carcasa               | Die-cast zinc  |
| Drain valve           | Semi-automatic   |
| Medic. valor de flujo | FV at P1 = 6 bar and pressure drop $\Delta p = 0.02$ bar |



## Nota

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.  
Otras especificaciones a petición.

## Descripción

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Artículo

| Denominación   | Rosca | Flujo de paso (L/min) | A (mm) | B        | C (mm) | D (mm) | DN |
|----------------|-------|-----------------------|--------|----------|--------|--------|----|
| K- 07 25 10 65 | G 1/8 | 130                   | 40,0   | 111,6 mm | 12,3   | 102,5  | 5  |
| K- 07 25 10 67 | G 1/4 | 160                   | 40,0   | 138,1 mm | 12,3   | 125,8  | 5  |

## Piezas de repuesto

|                        |                       |
|------------------------|-----------------------|
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-KOPPELPAKET MEHR     | Coupling packet       |