

K-MV O (NO) D 24 V DC STA

Normally open, (NO), directly operated, 24 V DC, standard type

HANSA FLEX

Características

Conexión eléctrica	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
Tipo de protecc.	IP 65
Temper. de medios	max. 80 °C when using water or oils; max. 90 °C when using with air
Descripción de rosca	G thread acc. DIN EN ISO 228-1
Carcasa, asiento de vál.	Brass
Piezas int.	Stainless steel
Obturac.	FPM



Nota

Otras especificaciones a petición.

Descripción

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Artículo

Denominación	Rosca	Presión de servicio máx. (bar)	NW	A (mm)	B (mm)	C (mm)	Forma constructiva
K- 07 30 01 86	G 1/8	7	3,0	70,0	40,0	76,0	2
K- 07 30 01 87	G 1/4	7	3,0	70,0	40,0	76,0	2
K- 07 30 01 88	G 3/8	7	5,0	85,0	52,0	92,0	2
K- 07 30 01 89	G 1/2	7	5,0	85,0	52,0	92,0	2