

# K-DRV ABLD GEW C RAENDEL

Unidirectional flow control valves, outgoing air restriction (»C«), screw connection

**HANSA FLEX**

## Características

|  |                                    |
|--|------------------------------------|
| Presión de servicio                        | máx. 10 bar                        |
| Rango de temperatura                       | 0 °C to +70 °C                     |
| Tomillo hueco, brazo glr., torn. regulador | Nickel-plated brass                |
| Piezas int.                                | Brass with a bare metal surface    |
| Junta labial anillo tórico                 | NBR                                |
| Juntas (imperdibles)                       | Polyamide (glass fibre-reinforced) |



## Nota

Otras especificaciones a petición.

## Descripción

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

## Artículo

| Denominación   | Conexión            | C<br>(mm) | Rosca | SW    | B<br>(mm) |
|----------------|---------------------|-----------|-------|-------|-----------|
| K- 07 15 04 57 | M 5 female thread   | 11,5      | M 5   | 8 mm  | 38,9      |
| K- 07 15 04 62 | G 1/8 female thread | 16,0      | G 1/8 | 14 mm | 42,0      |
| K- 07 15 04 58 | G 1/4 female thread | 22,0      | G 1/4 | 17 mm | 51,0      |
| K- 07 15 25 14 | G 1/2 female thread | 32,0      | G 1/2 | 26 mm | 81,0      |
| K- 07 15 25 15 | G 3/8 female thread | 26,0      | G 3/8 | 20 mm | 63,0      |