


# K-VHR 6KT MS NI

Hexagon head screw plugs

**HANSA FLEX**

## Características

|                         |  |
|-------------------------|--|
| Temperatura de servicio | Max. 150 °C                            |
| Presión                 | Max. 60 bar                            |
| Construcción            | Tapones roscados con hexágono exterior |
| Material                | Latón niquelado                        |



## Nota

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Otras especificaciones a petición.

## Descripción

Suitable for air, water, oil, steam, etc.

## Información adicional

Further types and dimensions on request.

## Artículo

| Denominación   | Rosca | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|-------|------------|------------|-------|
| K- 07 40 39 97 | M 5   | 7,0        | 4,0        | 8 mm  |
| K- 07 40 39 98 | G 1/8 | 10,0       | 6,0        | 14 mm |
| K- 07 40 39 99 | G 1/4 | 12,5       | 8,0        | 17 mm |
| K- 07 40 40 00 | G 3/8 | 13,5       | 9,0        | 19 mm |
| K- 07 40 40 01 | G 1/2 | 15,5       | 10,0       | 24 mm |
| K- 07 40 40 02 | G 3/4 | 16,5       | 11,0       | 30 mm |
| K- 07 40 39 96 | G 1   | 19,0       | 13,0       | 38 mm |