

K-SVKM NW 7,2 AG MS-BL CL

Quick disconnect couplings DN 7.2, brass with a bare metal surface, male

HANSA FLEX

Características

| | |
|--------------------------------------|---|
| Presión de servicio | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Temper. de medios | -20 °C to +100 °C |
| Carcasa, manguito, cuerpo válv | Brass |
| Material obturador | NBR |
| Muelles, anillo de muelle, pasadores | Stainless steel |



Nota

Otras especificaciones a petición.

Descripción

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. Compatible with CEJN 320, Rectus 25/26 and JWL 520/530. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Artículo

| Denominación | Conexión | Longitud (mm) | SW (mm) |
|----------------|------------|---------------|---------|
| K- 07 35 07 38 | G 1/8 male | 37,5 | 21 |
| K- 07 35 07 39 | G 1/4 male | 39,0 | 21 |
| K- 07 35 07 40 | G 3/8 male | 39,0 | 21 |
| K- 07 35 07 41 | G 1/2 male | 40,5 | 21 |