


K-XRD STECKANSCHLUSS Z SCH AGR-K BE

Straight non-return valves, flow direction from port to tube, conical male thread, coated

HANSA FLEX

Características

| | |
|---------------------------|--|
| Presión de funcionamiento | Max. 10 bar, vacuum |
| Campo de aplicación | Air, vacuum |
| Mangueras recomendadas | PU or PA (nylon) |
| Medios | aire comprimido |
| Norma | R thread acc. to ISO 7-1, thread coating |
| Rango de temperatura | 0 °C to +60 °C |
| Superficie de obturación | Conical version: thread coating |
| Material | Plastic, Nickel plated brass |
| Anillo de presión | Plastic |



Nota

Otras especificaciones a petición.

Descripción

The non-return function of these push-in fittings prevents the air from flowing back. the unidirectional design means air flow is only possible in one direction. These valves are available with air flow from the port to the tube or from the tube to the port.

Artículo

| Denominación | Rosca | para Ø exterior de tubo flexible | L1 (mm) | Presión de apertura (bar) | SW |
|----------------|-------|----------------------------------|---------|---------------------------|-------|
| K- 07 40 08 88 | R 1/8 | 4 mm | 24,0 | 0,2 | 10 mm |
| K- 07 40 08 89 | R 1/8 | 6 mm | 31,0 | 0,2 | 12 mm |
| K- 07 40 08 90 | R 1/8 | 8 mm | 32,8 | 0,2 | 14 mm |
| K- 07 40 08 86 | R 1/4 | 6 mm | 33,0 | 0,2 | 14 mm |
| K- 07 40 08 87 | R 1/4 | 8 mm | 34,8 | 0,2 | 14 mm |
| K- 07 40 08 91 | R 3/8 | 10 mm | 41,0 | 0,2 | 17 mm |
| K- 07 40 08 92 | R 3/8 | 12 mm | 42,5 | 0,2 | 21 mm |
| K- 07 40 08 84 | R 1/2 | 10 mm | 43,0 | 0,2 | 21 mm |
| K- 07 40 08 85 | R 1/2 | 12 mm | 44,5 | 0,2 | 21 mm |