


K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

HANSA FLEX

Características

| | |
|---|--|
| Presión de servicio | Max. 12 bar, maximum static working pressure (non-pulsating) |
| Pres. servicio manguitos ench. y casquillo | 0 to 35 bar |
| Flujo de aire | 1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temper. de medios | -20 °C to +60 °C |
| Carcasa, cuerpo válv | Nickel-plated brass |
| Válv. | Brass |
| Casquillo de desbloqueo | Plastic |
| Muelles, anillo de muelle, pasadores, bolas | Stainless steel |
| Material obturador | NBR |



Nota

Otras especificaciones a petición.

Descripción

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

Artículo

| Denominación | Conexión | Longitud (mm) | SW (mm) |
|----------------|---------------|---------------|---------|
| K- 07 35 03 04 | Stem, I.D. 6 | 71,2 | 22 |
| K- 07 35 03 05 | Stem, I.D. 8 | 71,2 | 22 |
| K- 07 35 03 06 | Stem, I.D. 9 | 71,2 | 22 |
| K- 07 35 03 07 | Stem, I.D. 10 | 71,2 | 22 |
| K- 07 35 03 08 | Stem, I.D. 13 | 71,2 | 22 |

Elementos adicionales

| | |
|----------------------------|---|
| K-NIPPEL KUPPL NW7 AG VZ | Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male |
| K-NIPPEL KUPPL NW7 IG VZ 2 | Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female |
| K-TUE 7,2 7,8 ST VZ 1 | Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, |