


K-V 340 IG IG

Unions 340, taper seat, female/female

HANSA FLEX

Características

Superficie	Hot dip galvanised
Rango de temperatura	-20 °C to +300 °C (at 20 bar)
Roscas interiores	acc. ISO 7-1
Material	Black malleable iron B350-10, design symbol A
Homologación	DIN DVGW



Nota

Otras especificaciones a petición.

Descripción

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Información adicional

Further types and dimensions on request.

Artículo

Denominación	Rosca
K- 07 40 38 19	Rp/Rp 1/4
K- 07 40 38 22	Rp/Rp 3/8
K- 07 40 38 18	Rp/Rp 1/2
K- 07 40 38 21	Rp/Rp 3/4
K- 07 40 38 15	Rp/Rp 1
K- 07 40 38 17	Rp/Rp 1 1/4
K- 07 40 38 16	Rp/Rp 1 1/2
K- 07 40 38 20	Rp/Rp 2
K- 07 40 52 37	Rp/Rp 2 1/2
K- 07 40 52 38	Rp/Rp 3