


K-Y-WINKELVERSCH DER IG AG-K

Male branch Y-elbows, swivel type, parallel female thread and conical male thread, coated



Características	
Presión de funcionamiento	Max. 15 bar, coarse vacuum
Campo de aplicación	Air, vacuum
Mangueras recomendadas	PU or PA (nylon)
Medios	Compressed air and all gases or liquids that are compatible with the materials
Rango de temperatura	-20 °C to +80 °C
Superficie de obturación	Conical version: thread coating
Material	Plastic, Nickel plated brass
Anillo de presión	Plastic



Nota
Otras especificaciones a petición.

Descripción
Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artículo					
Denominación	Rosca	para Ø exterior de tubo flexible	L1 (mm)	L2 (mm)	SW
K- 07 40 43 23	G/R 1/8	6 mm	24,0	30,5	14 mm
K- 07 40 43 22	G/R 1/4	8 mm	28,5	36,0	17 mm
K- 07 40 43 24	G/R 3/8	10 mm	33,7	42,3	21 mm
K- 07 40 43 21	G/R 1/2	12 mm	37,5	51,0	24 mm