

K-WV 3/2 LB NAMUR

3/2-way spool valves with NAMUR style interface, NC

HANSA FLEX

Características

| | |
|--------------------------------------|---|
| Medios | Air, neutral gases, filtered |
| Presión de funcionamiento | 1.5 to 10 bar |
| Temperatura de servicio | -20 °C to +70 °C |
| Conexión eléctrica | Plug connector PG 9 |
| Incluido en el volumen de suministro | Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws |
| Consumo de potencia | 3 W=5 VA~ |
| Carcasa | Aluminium, anodised |
| Corredera | Stainless steel |
| Material obturador | NBR |



Nota

Otras especificaciones a petición.

Descripción

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Artículo

| Denominación | Tensión | Conexión | DN | Flujo de paso (L/min) |
|----------------|--------------|----------|----|-----------------------|
| K- 07 15 00 03 | 230 V, 50 Hz | G 1/4 | 7 | 1250 |
| K- 07 15 00 04 | 24 V DC | G 1/4 | 7 | 1250 |