

K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

HANSA FLEX

Características

| | |
|---|---|
| Medios | Air, neutral gases, filtered |
| Presión de funcionamiento | 0.5 to 10 bar |
| Temperatura de servicio | -20 °C to +70 °C |
| Incluido en el volumen de suministro | 1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws |
| Carcasa | Aluminium, anodised |
| Material | Obturación: NBR |
| Material obturador | NBR |



Nota

Otras especificaciones a petición.

Descripción

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Artículo

| Denominación | Función | Accionam. | DN | Flujo de paso (L/min) |
|----------------|---------|---------------|----|--------------------------|
| K- 07 15 22 39 | 3/2-way | Knurled Screw | 5 | 650 |
| K- 07 15 22 40 | 3/2-way | Screwdriver | 5 | 650 |
| K- 07 15 22 41 | 5/2-way | Knurled Screw | 5 | 650 |
| K- 07 15 22 42 | 5/2-way | Screwdriver | 5 | 650 |