

K-MANO STAND H

Pressure gauges, CrNi steel, standard type, connection on rear, central

HANSA FLEX

Características

| | |
|----------------------|---|
| Tipo | 131.11 |
| Versión | Bourdon-tube pressure gauge, CrNi steel type |
| Aplicación | For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction |
| Categoría de calidad | 2,5 |
| Temper. de medios | max. +100 °C |
| Temp. entorno | -40 °C to +60 °C |
| Carcasa | CrNi steel |
| Ventana de insp. | Polycarbonate |



Nota

Otras especificaciones a petición.

Descripción

Standard model manufactured entirely from CrNi steel, economical and reliable.

Artículo

| Denominación | Rango de medición | Ø (mm) | Conexión |
|----------------|-------------------|--------|----------|
| K- 07 20 03 93 | 0 - 1.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 94 | 0 - 1.6 bar | 40,0 | G 1/4 |
| K- 07 20 03 95 | 0 - 2.5 bar | 40,0 | G 1/4 |
| K- 07 20 03 96 | 0 - 4.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 97 | 0 - 6.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 98 | 0 - 10.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 99 | 0 - 16.0 bar | 40,0 | G 1/4 |
| K- 07 20 04 00 | 0 - 25.0 bar | 40,0 | G 1/4 |
| K- 07 20 04 01 | 0 - 40.0 bar | 40,0 | G 1/4 |
| K- 07 20 04 02 | 0 - 60.0 bar | 40,0 | G 1/4 |
| K- 07 20 04 03 | 0 - 100.0 bar | 40,0 | G 1/4 |
| K- 07 20 04 94 | 0 - 1.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 95 | 0 - 1.6 bar | 50,0 | G 1/4 |
| K- 07 20 04 96 | 0 - 2.5 bar | 50,0 | G 1/4 |
| K- 07 20 04 97 | 0 - 4.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 98 | 0 - 6.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 99 | 0 - 10.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 00 | 0 - 16.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 01 | 0 - 25.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 02 | 0 - 40.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 03 | 0 - 60.0 bar | 50,0 | G 1/4 |
| K- 07 20 05 04 | 0 - 100.0 bar | 50,0 | G 1/4 |