

K-SVKM NW 7,2 DREH MS-NI

Quick disconnect couplings DN 7.2, nickel-plated brass, swivel type

HANSA FLEX

Características

Presión de servicio	0 - 35 bar, maximum static working pressure (non-pulsating)
Flujo de aire	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temper. de medios	0 °C to +70 °C
Carcasa, manguito	Nickel-plated brass
Válv.	Brass with a bare metal surface
Muelles, anillo de muelle	Stainless steel 1.4310
Pasadores de cierre	Stainless steel 1.4034
Material obturador	NBR



Nota

Otras especificaciones a petición.

Descripción

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Artículo

Denominación	Conexión	Longitud (mm)
K- 07 35 07 28	Stem 6 mm, swivel type	74,0
K- 07 35 07 29	Stem 8 mm, swivel type	74,0
K- 07 35 07 30	Stem 9 mm, swivel type	74,0
K- 07 35 07 31	Stem, 10 mm, swivel type	74,0
K- 07 35 07 32	Stem, 13 mm, swivel type	74,0

Elementos adicionales

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass