

K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

HANSA FLEX

Características

| | |
|----------------------------------|---------------------------------------|
| Presión de servicio | 0 - 35 bar |
| Flujo de aire | 2.100 l/min (at $\Delta p = 0.5$ bar) |
| Temper. de medios | -20 °C to +40 °C |
| Pieza roscada | Nickel-plated brass |
| Cuerpo de válv. | Steel, QPQ treated |
| Casquillo de desbloqueo | Extremely robust, ergonomic plastic |
| Válv., asiento | Brass |
| Medios | Only for clean compressed air |
| Juntas | NBR |
| Muelles, anillo de muelle, bolas | stain less steel |



Nota

Otras especificaciones a petición.

Descripción

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Artículo

| Denominación | Conexión | Longitud (mm) | SW (mm) |
|----------------|--------------|------------------|------------|
| K- 07 35 08 50 | G 1/4 female | 59,0 | 19 |
| K- 07 35 08 51 | G 3/8 female | 59,0 | 19 |
| K- 07 35 08 52 | G 1/2 female | 62,0 | 24 |

Elementos adicionales

| | |
|-------------------------------|--|
| K-NIPP KUPPL NW7 SCHL MS NI K | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring |
| K-NIPPEL KUPPL NW7 AG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male |
| K-NIPPEL KUPPL NW7 IG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female |
| K-NIPPEL KUPPL NW7 SCHL MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose |
| K-TUE 7,2 7,8 MS NI | Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass |