

K-PRAEZIONS STEUERREGLER

Precision pilot regulators (feedback)

HANSA FLEX

Características

| | |
|------------------------|-----------------------|
| Presión de entrada | Max. 16 bar |
| Temper. de medios | max. 80 °C |
| Temp. entorno | Max. 80 °C |
| Conex. manómetro | For feedback pressure |
| Material obturador | FKM |
| Carcasa | Die-cast zinc |
| Membrana | FKM |
| Consumo de aire propio | 3 to 6 l/min |



Nota

Otras especificaciones a petición.

Descripción

Diaphragm pressure regulator for feedback systems, specially designed for use in a pneumatically controlled closed control loop in combination with a pressure regulator with pneumatic remote control, e.g. our Art. Nos. K-07250505 to K-07250510.

Artículo

| Denominación | Rosca | Rango de regulación | A (mm) | B | C (mm) | D (mm) |
|----------------|-------|---------------------|-----------|----------|-----------|-----------|
| K- 07 25 05 11 | G 1/4 | 0.2 - 7 bar | 82,0 | 142,8 mm | 19,4 | 123,4 |

Accesorios

| | |
|--------------------------|--------|
| K-HALTERBAUSATZ STANDARD | Holder |
|--------------------------|--------|