

K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption

HANSA FLEX

Características

Presión de entrada	Max. 16 bar
Temper. de medios	max. 80 °C
Temp. entorno	Max. 80 °C
Medios	Fine-filtered (5 µm), unlubricated compressed air, neutral gases
Conex. manómetro	G 1/4
Material obturador	NBR
Carcasa	Die-cast zinc
Cono de válv., membrana	FPM



Nota

Otras especificaciones a petición.

Descripción

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

Artículo

Denominación	Rosca	Rango de regulación	Flujo de paso (L/min)	A (mm)	B	C (mm)	D (mm)
K- 07 25 09 39	G 1/4	0 - 1 bar	600	82,0	148,0 mm	19,5	128,5
K- 07 25 09 40	G 1/4	0.1 - 3 bar	760	82,0	148,0 mm	19,5	128,5
K- 07 25 09 41	G 1/4	0.2 - 6 bar	550	82,0	148,0 mm	19,5	128,5
K- 07 25 09 42	G 1/4	0.5 - 10 bar	400	82,0	148,0 mm	19,5	128,5

Accesorios

K-HALTERBAUSATZ STANDARD Holder