


# K-WTEH SERIE ONE O DRS

Service units, »ONE« Series, without pressure switch

**HANSA FLEX**

## Características

Presión de entrada	Max. 10 bar
Rango de temperatura	-10 °C to +50 °C
Medios	aire comprimido
Tipo de protecc.	IP 65
Presión de funcionamiento	0.5 - 8 bar
Interr pres	Changeover contact
Ancho de poros en elemento filtrante	20 µm
Medic. valor de flujo	At 6,3 bar and $\Delta p = 1$ bar



## Nota

Otras especificaciones a petición.

## Descripción

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

## Indicaciones para pedidos

This unit can also be supplied with many other combinations of functions and port sizes. We will be pleased to make you an offer to match your individual specification on request!

## Artículo

Denominación	Conexión	Flujo de paso (L/min)	A (mm)	B	C (mm)	Tensión
K- 07 25 13 79	G 1/4	2400	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 80	G 3/8	3300	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 81	G 1/2"	4000	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)