


K-VSTO POM

Plugs

Características

| | |
|---------------------------|---|
| Presión de funcionamiento | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm) |
| Temperatura de servicio | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| Material | Acetalpolymerisat (POM) |
| Material obturador | NBR |



Nota

Otras especificaciones a petición.

Descripción

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Artículo

| Denominación | Color | L1 (mm) | Tubul. (mm) |
|----------------|-------|------------|----------------|
| K- 07 40 29 11 | rojo | 28,0 | 4 |
| K- 07 40 29 12 | rojo | 28,0 | 5 |
| K- 07 40 29 13 | rojo | 30,0 | 6 |
| K- 07 40 29 14 | rojo | 31,0 | 8 |
| K- 07 40 29 15 | rojo | 36,5 | 10 |
| K- 07 40 29 16 | rojo | 38,5 | 12 |
| K- 07 40 29 17 | negro | 45,0 | 15 |
| K- 07 40 29 18 | negro | 41,5 | 18 |
| K- 07 40 29 19 | negro | 45,0 | 22 |
| K- 07 40 29 20 | negro | 56,0 | 28 |