


K-LKM S NW7,6 AG

Safety couplings DN 7.6, male

HANSA FLEX

Características

Presión de servicio	Max. 16 bar
Flujo de aire	2.250 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temper. de medios	-20 °C to +100 °C
Material	Galvanised steel / brass
Muell	Stainless-steel
Material obturador	NBR



Nota

Otras especificaciones a petición.

Descripción

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rates and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414.

Artículo

Denominación	Conexión	Longitud (mm)	SW (mm)
K- 07 35 13 19	R 1/4 male	63,0	20
K- 07 35 13 21	R 3/8 male	61,0	20
K- 07 35 13 16	R 1/2 male	55,5	22

Elementos adicionales

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel