

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982

HANSA FLEX

Características

| | |
|---------------------------|---------------------------|
| Presión de funcionamiento | Max. 50 bar |
| Superficie | Hot dip galvanised |
| Roscas interiores | acc. ISO 7-1 |
| Material | Zinc plated steel ST 37-2 |



Nota

Otras especificaciones a petición.

Descripción

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Artículo

| Denominación | Rosca | Longitud (mm) |
|----------------|-------|---------------|
| K- 07 40 35 71 | R 1/4 | 40,0 |
| K- 07 40 35 72 | R 1/4 | 60,0 |
| K- 07 40 35 73 | R 1/4 | 80,0 |
| K- 07 40 35 66 | R 1/4 | 100,0 |
| K- 07 40 35 67 | R 1/4 | 120,0 |
| K- 07 40 35 68 | R 1/4 | 150,0 |
| K- 07 40 35 69 | R 1/4 | 180,0 |
| K- 07 40 35 70 | R 1/4 | 200,0 |
| K- 07 40 35 95 | R 3/8 | 40,0 |
| K- 07 40 35 96 | R 3/8 | 60,0 |
| K- 07 40 35 97 | R 3/8 | 80,0 |
| K- 07 40 35 90 | R 3/8 | 100,0 |
| K- 07 40 35 91 | R 3/8 | 120,0 |
| K- 07 40 35 92 | R 3/8 | 150,0 |
| K- 07 40 35 93 | R 3/8 | 180,0 |
| K- 07 40 35 94 | R 3/8 | 200,0 |
| K- 07 40 35 63 | R 1/2 | 40,0 |
| K- 07 40 35 64 | R 1/2 | 60,0 |
| K- 07 40 35 65 | R 1/2 | 80,0 |
| K- 07 40 35 58 | R 1/2 | 100,0 |
| K- 07 40 35 59 | R 1/2 | 120,0 |
| K- 07 40 35 60 | R 1/2 | 150,0 |
| K- 07 40 35 61 | R 1/2 | 180,0 |
| K- 07 40 35 62 | R 1/2 | 200,0 |
| K- 07 40 35 87 | R 3/4 | 40,0 |
| K- 07 40 35 88 | R 3/4 | 60,0 |
| K- 07 40 35 89 | R 3/4 | 80,0 |
| K- 07 40 35 82 | R 3/4 | 100,0 |
| K- 07 40 35 83 | R 3/4 | 120,0 |
| K- 07 40 35 84 | R 3/4 | 150,0 |
| K- 07 40 35 85 | R 3/4 | 180,0 |
| K- 07 40 35 86 | R 3/4 | 200,0 |
| K- 07 40 35 39 | R 1 | 40,0 |
| K- 07 40 35 40 | R 1 | 60,0 |
| K- 07 40 35 41 | R 1 | 80,0 |
| K- 07 40 35 34 | R 1 | 100,0 |
| K- 07 40 35 35 | R 1 | 120,0 |
| K- 07 40 35 36 | R 1 | 150,0 |

K-ROHRDOPPELNIPPEL 23 AG ST37 VZ

Double pipe nipples 23, male/male, zinc plated steel ST 37-2, DIN 2982



Artículo

| Denominación | Rosca | Longitud (mm) |
|----------------|---------|---------------|
| K- 07 40 35 37 | R 1 | 180,0 |
| K- 07 40 35 38 | R 1 | 200,0 |
| K- 07 40 35 55 | R 1 1/4 | 40,0 |
| K- 07 40 35 56 | R 1 1/4 | 60,0 |
| K- 07 40 35 57 | R 1 1/4 | 80,0 |
| K- 07 40 35 50 | R 1 1/4 | 100,0 |
| K- 07 40 35 51 | R 1 1/4 | 120,0 |
| K- 07 40 35 52 | R 1 1/4 | 150,0 |
| K- 07 40 35 53 | R 1 1/4 | 180,0 |
| K- 07 40 35 54 | R 1 1/4 | 200,0 |
| K- 07 40 35 47 | R 1 1/2 | 40,0 |
| K- 07 40 35 48 | R 1 1/2 | 60,0 |
| K- 07 40 35 49 | R 1 1/2 | 80,0 |
| K- 07 40 35 42 | R 1 1/2 | 100,0 |
| K- 07 40 35 43 | R 1 1/2 | 120,0 |
| K- 07 40 35 44 | R 1 1/2 | 150,0 |
| K- 07 40 35 45 | R 1 1/2 | 180,0 |
| K- 07 40 35 46 | R 1 1/2 | 200,0 |
| K- 07 40 35 79 | R 2 | 40,0 |
| K- 07 40 35 80 | R 2 | 60,0 |
| K- 07 40 35 81 | R 2 | 80,0 |
| K- 07 40 35 74 | R 2 | 100,0 |
| K- 07 40 35 75 | R 2 | 120,0 |
| K- 07 40 35 76 | R 2 | 150,0 |
| K- 07 40 35 77 | R 2 | 180,0 |
| K- 07 40 35 78 | R 2 | 200,0 |
| K- 07 40 50 93 | R 2 1/2 | 80,0 |
| K- 07 40 50 88 | R 2 1/2 | 100,0 |
| K- 07 40 50 89 | R 2 1/2 | 120,0 |
| K- 07 40 50 90 | R 2 1/2 | 150,0 |
| K- 07 40 50 91 | R 2 1/2 | 180,0 |
| K- 07 40 50 92 | R 2 1/2 | 200,0 |
| K- 07 40 50 99 | R 3 | 80,0 |
| K- 07 40 50 94 | R 3 | 100,0 |
| K- 07 40 50 95 | R 3 | 120,0 |
| K- 07 40 50 96 | R 3 | 150,0 |
| K- 07 40 50 97 | R 3 | 180,0 |
| K- 07 40 50 98 | R 3 | 200,0 |