

K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type

HANSA FLEX

Características

Presión de servicio	máx. 10 bar
Flujo de aire	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temper. de medios	-20 °C to +150 °C
Carcasa	Stainless steel 1.4404
Rosca	Stainless steel 1.4404
Piezas int.	Stainless steel 1.4404
Botón, válv.	Stainless steel 1.4404
Material obturador	FKM



Nota

Not suitable for hitting / pulsating tools.
Otras especificaciones a petición.

Descripción

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Información adicional

Not suitable for hitting / pulsating tools.

Artículo

Denominación	Conexión	Longitud (mm)	SW (mm)
K- 07 35 12 76	G 1/4 male	70,5	21
K- 07 35 12 77	G 3/8 male	70,0	21
K- 07 35 12 78	G 1/2 male	72,5	25