

K-LKM S NW7,4 DREH SCHL TUE VA

Safety couplings DN 7.4, stainless steel 1.4404, with hose stem, swivel type

HANSA FLEX

Características

| | |
|---------------------|---|
| Presión de servicio | máx. 10 bar |
| Flujo de aire | 1.800 l/min (at 6 bar and $\Delta p = 1$ bar) |
| Temper. de medios | -20 °C to +150 °C |
| Carcasa | Stainless steel 1.4404 |
| Rosca | Stainless steel 1.4404 |
| Piezas int. | Stainless steel 1.4404 |
| Botón, válv. | Stainless steel 1.4404 |
| Material obturador | FKM |



Nota

Not suitable for hitting / pulsating tools.
Otras especificaciones a petición.

Descripción

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Información adicional

Not suitable for hitting / pulsating tools.

Artículo

| Denominación | Conexión | Longitud (mm) | SW (mm) |
|----------------|---------------|---------------|---------|
| K- 07 35 12 83 | Stem, I.D. 6 | 88,5 | 21 |
| K- 07 35 12 85 | Stem, I.D. 9 | 88,5 | 21 |
| K- 07 35 12 86 | Stem, I.D. 13 | 88,5 | 21 |