

# K-L-STECK VB VA

Union elbows

**HANSA FLEX**

## Características

|                              |   |
|------------------------------|---|
| Presión de func. pulsante    | Max. 10 bar   |
| Presión                      | Max. 15 bar (depending on pipe quality)                         |
| Material de tubería adecuado | PVDF, PTFE, stainless steel, PA, PU                             |
| Temp. entorno                | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Material                     | Acero fino 1.4404   |
| Material obturador           | FKM   |



## Nota

Otras especificaciones a petición.

## Descripción

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Artículo

| Denominación   | para Ø exterior de tubo flexible | L1<br>(mm) | L2<br>(mm) |
|----------------|----------------------------------|------------|------------|
| K- 07 40 24 20 | 4 mm                             | 17,0       | 17,0       |
| K- 07 40 24 21 | 6 mm                             | 20,0       | 20,0       |
| K- 07 40 24 22 | 8 mm                             | 21,0       | 21,0       |
| K- 07 40 24 23 | 10 mm                            | 25,0       | 25,0       |
| K- 07 40 24 24 | 12 mm                            | 27,0       | 27,0       |