


K-T-STECK VERS ISK DREH AG OR1

Male branch tees with inner hex, swivel type, parallel male thread with O-ring



Características	
Presión de funcionamiento	Max. 15 bar, coarse vacuum
Campo de aplicación	Air, vacuum
Mangueras recomendadas	PU or PA (nylon)
Medios	Compressed air and all gases or liquids that are compatible with the materials
Rango de temperatura	-20 °C to +80 °C
Superficie de obturación	Parallel version: O-ring in housing
Material	Plastic, Nickel plated brass
Anillo de presión	Plastic



Nota
Otras especificaciones a petición.

Descripción
Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artículo						
Denominación	Rosca	para Ø exterior de tubo flexible	Hexágono int. (mm)	L1 (mm)	L2 (mm)	SW
K- 07 40 06 21	G 1/8	4 mm	4,0	45,0	28,5	14 mm
K- 07 40 06 22	G 1/8	6 mm	4,0	42,6	28,5	14 mm
K- 07 40 06 23	G 1/8	8 mm	4,0	48,5	28,5	14 mm
K- 07 40 06 19	G 1/4	6 mm	6,0	46,7	37,5	17 mm
K- 07 40 06 20	G 1/4	8 mm	6,0	52,5	37,5	17 mm
K- 07 40 06 17	G 1/4	10 mm	6,0	59,6	37,5	17 mm
K- 07 40 06 18	G 1/4	12 mm	6,0	60,7	37,5	17 mm
K- 07 40 06 26	G 3/8	8 mm	8,0	56,3	39,2	20 mm
K- 07 40 06 24	G 3/8	10 mm	8,0	63,5	39,2	20 mm
K- 07 40 06 25	G 3/8	12 mm	8,0	64,9	39,2	20 mm