

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Características

Capa interna	Soft-PVC, black
Inserción	Malla de poliéster
Capa externa	Soft-PVC, blue
Temperatura	-20 °C to +60 °C
Longitud rollo	50 m



Nota

Otras especificaciones a petición.

Descripción

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Artículo

Denominación	Ø Manguera int. (mm)	Ø Manguera ext. (mm)	Max. working pressure resistance at 23°C (bar)	Radio mín. de flexión (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88