K-LECKAGESUCHGERAET
Leakage finder

Características

Frecuencia de trabajo	40 kHz ± 2 kHz
Conexión	4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable
Láser	Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW
Suministro de energía	Internal NiMH rechargeable battery
Tiempo de func.	Approx. 6 hours without laser / 4 hours with laser
Tiempo de carga	Approx. 1.5 hours
Temperatura de servicio	0 °C to +40 °C
Temp. almac.	-10 °C to +50 °C



Nota

Otras especificaciones a petición.

Descripción

Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems.
The advantages of the LS 100: Simple and quick measurement, even from distances of several metres Measurements can be taken on running systems, without affecting their operation
The device is quickly amortised by the high cost savings

Artículo

Denominación	Descripción
K- 07 25 19 53	Leak detection device, including accessories in a practical carrying case

Accesorios

K-ALU-TELESKOPSTANGE	Aluminium-telescopic pole

Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.