K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Características

Aplicación	Air, gases, oils, greases, fuels, organic and inorganic substances
Temperatura de servicio	-40 °C to +100 °C
Tipo de conexión	connection nipples and coupling NW 7,2



Nota

Otras especificaciones a petición.

Descripción

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artículo

Denominación	Ø Manguera int. (mm)	Ø Manguera ext. (mm)	Ø Espiral ext. (mm)	Torsiones	Max. working pressure resistance at 23° C (bar)	Longitud máx. de trabajo (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Accesorios

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.