

K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug,
bare brass

HANSA FLEX

Características

Tipo de conexión	connection nipples and coupling NW 7,2
Temperatura de servicio	-40 °C to +74 °C



Nota

Otras especificaciones a petición.

Descripción

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Artículo

Denominación	Ø Manguera int. (mm)	Ø Manguera ext. (mm)	Ø espira exterior (mm)	Max. working pressure resistance at 23°C (bar)	Longitud máx. de trabajo (m)
K- 07 10 12 72	5,0	8,0	40	10	3,0
K- 07 10 12 74	5,0	8,0	40	10	6,0
K- 07 10 12 76	5,0	8,0	40	10	7,5
K- 07 10 12 81	6,3	9,5	60	10	3,0
K- 07 10 12 83	6,3	9,5	60	10	6,0
K- 07 10 12 85	6,3	9,5	60	10	7,5
K- 07 10 12 79	6,3	9,5	60	10	10,0
K- 07 10 12 90	8,0	12,0	80	9	3,0
K- 07 10 12 92	8,0	12,0	80	9	6,0
K- 07 10 12 94	8,0	12,0	80	9	7,5
K- 07 10 12 88	8,0	12,0	80	9	10,0

Accesorios

K-DREHBARE VERSCHRAUBUNG	Swivel adapters
--------------------------	-----------------