K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

Características

Tipo de conexión	with pushbutton safety coupling NW 7,4 steel nipple galvanised
Temperatura de servicio	-40 °C to +74 °C



Nota

Otras especificaciones a petición.

Descripción

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.
¡No adecuado para herramientas percutoras o pulsantes!

Artículo

Denominación	Ø Manguera int. (mm)	Ø Manguera ext. (mm)	Ø espira exterior (mm)	Max. working pressure resistance at 23°C (bar)	Longitud máx. de trabajo (m)
K- 07 10 12 71	5,0	8,0	40	10	3,0
K- 07 10 12 73	5,0	8,0	40	10	6,0
K- 07 10 12 75	5,0	8,0	40	10	7,5
K- 07 10 12 80	6,3	9,5	60	10	3,0
K- 07 10 12 82	6,3	9,5	60	10	6,0
K- 07 10 12 84	6,3	9,5	60	10	7,5
K- 07 10 12 78	6,3	9,5	60	10	10,0
K- 07 10 12 89	8,0	12,0	80	9	3,0
K- 07 10 12 91	8,0	12,0	80	9	6,0
K- 07 10 12 93	8,0	12,0	80	9	7,5
K- 07 10 12 87	8,0	12,0	80	9	10,0

Accesorios

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.