

K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

HANSA FLEX

Características

Capa interna	Soft-PVC, red, oil resistant
Inserción	Malla de poliéster
Capa externa	Soft-PVC, black, oil resistant
Temperatura	-20 °C to +60 °C
Longitud rollo	50 m



Nota

Otras especificaciones a petición.

Descripción

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

Artículo

Denominación	Ø Manguera int. (mm)	Ø Manguera ext. (mm)	Max. working pressure resistance at 23°C (bar)	Radio mín. de flexión (mm)
K- 07 10 10 41	6,3	11,0	16	18
K- 07 10 10 42	8,0	13,0	16	25
K- 07 10 10 43	9,0	14,5	16	25
K- 07 10 10 44	10,0	15,5	16	35
K- 07 10 10 45	12,7	19,0	16	50
K- 07 10 10 46	16,0	23,0	16	70
K- 07 10 10 47	19,0	26,5	16	70
K- 07 10 10 48	25,0	33,5	16	120