

K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

HANSA FLEX

Características

| | |
|----------------|--------------------------------|
| Capa interna | Soft-PVC, red, oil resistant |
| Inserción | Malla de poliéster |
| Capa externa | Soft-PVC, black, oil resistant |
| Temperatura | -20 °C to +60 °C |
| Longitud rollo | 50 m |



Nota

Otras especificaciones a petición.

Descripción

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

Artículo

| Denominación | Ø Manguera int. (mm) | Ø Manguera ext. (mm) | Max. working pressure resistance at 23°C (bar) | Radio mín. de flexión (mm) |
|----------------|-------------------------|-------------------------|---|-------------------------------|
| K- 07 10 10 41 | 6,3 | 11,0 | 16 | 18 |
| K- 07 10 10 42 | 8,0 | 13,0 | 16 | 25 |
| K- 07 10 10 43 | 9,0 | 14,5 | 16 | 25 |
| K- 07 10 10 44 | 10,0 | 15,5 | 16 | 35 |
| K- 07 10 10 45 | 12,7 | 19,0 | 16 | 50 |
| K- 07 10 10 46 | 16,0 | 23,0 | 16 | 70 |
| K- 07 10 10 47 | 19,0 | 26,5 | 16 | 70 |
| K- 07 10 10 48 | 25,0 | 33,5 | 16 | 120 |