

# K-T STECK VB SCHANH IG 20-63 INFI

T-push-in connector Ø 20 mm – Ø 63 mm with integrated gooseneck and internal thread

**HANSA FLEX**

## Características

<b>Medios</b>	Compressed air, vacuum, inert gases
<b>Presión de servicio</b>	-0,99 bar - 15 bar
<b>Rango de temperatura</b>	-20 °C to +80 °C
<b>Obturac.</b>	NBR
<b>Carcasa</b>	Nickel-plated brass
<b>Anillo de apriete</b>	Stainless steel 1.4301
<b>Tuerca</b>	Nickel-plated brass
<b>Junta tórica</b>	NBR
<b>Anillos de fijación</b>	Technopolymer



## Artículo

Denominación	Ø exterior tubo	Conexión	A (mm)	B (mm)	C (mm)	E (mm)	L1 (mm)	L2 (mm)	SW (mm)	SW1 (mm)
<b>K- 07 40 54 04</b>	20 mm	G 3/8	11,0	31,5	48,0	34,5	109,0	25,0	28	30
<b>K- 07 40 54 05</b>	20 mm	G 1/2"	13,5	31,5	48,0	34,5	109,0	28,0	28	30
<b>K- 07 40 54 06</b>	25 mm	G 3/8	11,0	38,5	45,5	42,5	121,5	29,0	35	35
<b>K- 07 40 54 07</b>	25 mm	G 1/2"	13,5	38,5	45,5	42,5	121,5	31,0	35	35
<b>K- 07 40 54 08</b>	32 mm	G 1/2"	13,5	46,0	54,5	52,0	146,5	36,5	45	45
<b>K- 07 40 54 09</b>	40 mm	G 1/2"	13,5	52,5	60,0	63,0	165,5	41,5	55	55
<b>K- 07 40 54 10</b>	50 mm	G 3/4	14,5	63,5	73,5	73,0	201,0	47,5	65	65