


K-PNEUMA KOMPAKTSCHLITTEN MXS

Air Slide Table MXS

HANSA FLEX

Características

| | |
|--------------------------|--|
| presión de servicio máx. | 0,7 MPa |
| Presión mín. de servicio | 0.15 MPa |
| Amortiguación | elastic stop |
| Función | double working |
| Presión de prueba | 1,05 MPa |
| Temper. de medios | -10 °C to +60 °C |
| Temp. entorno | -10 °C to +60 °C |
| Velocidad del émbolo | 50 to 500 mm/s |
| Medios | aire comprimido |
| Serie | MXS |
| Otras especif. | Carriage and air cylinder as a complete unit Ideal for precision assembly applications High resistance to the cultivation of loads |



Descripción

Compact air slide table, series MXS, slide table and air cylinder as complete unit, ideal for precise installation applications, high resistance capacity when building up loads, with stroke limiting unit or shock absorber, (order separately), no stroke adjustment, double action, piston diameter / stroke: 20/100 mm, connection size: G 1/8

Artículo

| Denominación | Ø pistón (mm) | Carrera (mm) | Conex. neumática | Peso (kg) |
|----------------|---------------|--------------|------------------|-----------|
| K- 07 55 01 46 | 6 | 10 | M 3 | 0,080 |
| K- 07 55 01 47 | 6 | 20 | M 3 | 0,100 |
| K- 07 55 01 48 | 6 | 30 | M 3 | 0,115 |
| K- 07 55 01 49 | 6 | 40 | M 3 | 0,155 |
| K- 07 55 01 50 | 6 | 50 | M 3 | 0,180 |
| K- 07 55 01 52 | 8 | 10 | M 5 | 0,150 |
| K- 07 55 01 53 | 8 | 20 | M 5 | 0,160 |
| K- 07 55 01 54 | 8 | 30 | M 5 | 0,190 |
| K- 07 55 01 55 | 8 | 40 | M 5 | 0,235 |
| K- 07 55 01 56 | 8 | 50 | M 5 | 0,285 |
| K- 07 55 01 57 | 8 | 75 | M 5 | 0,410 |
| K- 07 55 01 27 | 12 | 10 | M 5 | 0,325 |
| K- 07 55 01 29 | 12 | 20 | M 5 | 0,325 |
| K- 07 55 01 30 | 12 | 30 | M 5 | 0,325 |
| K- 07 55 01 31 | 12 | 40 | M 5 | 0,385 |
| K- 07 55 01 32 | 12 | 50 | M 5 | 0,485 |
| K- 07 55 01 33 | 12 | 75 | M 5 | 0,660 |
| K- 07 55 01 28 | 12 | 100 | M 5 | 0,890 |
| K- 07 55 01 35 | 16 | 10 | M 5 | 0,570 |
| K- 07 55 01 38 | 16 | 20 | M 5 | 0,570 |
| K- 07 55 01 39 | 16 | 30 | M 5 | 0,580 |
| K- 07 55 01 40 | 16 | 40 | M 5 | 0,640 |
| K- 07 55 01 41 | 16 | 50 | M 5 | 0,760 |
| K- 07 55 01 42 | 16 | 75 | M 5 | 1,090 |
| K- 07 55 01 36 | 16 | 100 | M 5 | 0,770 |
| K- 07 55 01 37 | 16 | 125 | M 5 | 0,900 |
| K- 07 55 00 01 | 20 | 10 | G 1/8 | 0,960 |
| K- 07 55 00 05 | 20 | 20 | G 1/8 | 0,980 |
| K- 07 55 00 06 | 20 | 30 | G 1/8 | 1,010 |
| K- 07 55 00 07 | 20 | 40 | G 1/8 | 1,100 |
| K- 07 55 00 08 | 20 | 50 | G 1/8 | 1,250 |
| K- 07 55 00 09 | 20 | 75 | G 1/8 | - |
| K- 07 55 00 02 | 20 | 100 | G 1/8 | 2,150 |
| K- 07 55 00 03 | 20 | 125 | G 1/8 | 2,670 |
| K- 07 55 00 04 | 20 | 150 | G 1/8 | 3,190 |



Hemos revisado cuidadosamente esta publicación, pero no obstante no podemos excluir los errores y no garantizamos los datos que constan aquí.

28.06.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-PNEUMA KOMPAKTSCHLITTEN MXS

Air Slide Table MXS



Artículo

| Denominación | Ø pistón (mm) | Carrera (mm) | Conex. neumática | Peso (kg) |
|----------------|------------------|-----------------|------------------|--------------|
| K- 07 55 00 10 | 25 | 10 | G 1/8 | 1,660 |
| K- 07 55 00 14 | 25 | 20 | G 1/8 | 1,680 |
| K- 07 55 00 15 | 25 | 30 | G 1/8 | 1,690 |
| K- 07 55 00 16 | 25 | 40 | G 1/8 | 1,840 |
| K- 07 55 00 17 | 25 | 50 | G 1/8 | 2,090 |
| K- 07 55 00 18 | 25 | 75 | G 1/8 | 2,650 |
| K- 07 55 00 11 | 25 | 100 | G 1/8 | 3,270 |
| K- 07 55 00 12 | 25 | 125 | G 1/8 | 4,140 |
| K- 07 55 00 13 | 25 | 150 | G 1/8 | 4,170 |