

LKM IR ST DK

Manguito de acoplamiento insertable (aire) con seguro

HANSA FLEX

Características

Construcción	Manguito para acoplamiento de cierre rápido
Conexión 1	Rosca interior BSP cilíndricas
Conexión 2	
Presión de servicio	máx. 12 bares
Flujo de aire	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temper. de medios	-20 °C to +70 °C
Carcasa	Aluminium, anodised
Rosca	Nickel-plated brass
Piezas int.	Stainless steel
Botón, válv.	Hardened, galvanised steel
Material obturador	NBR



Nota

Not suitable for hitting / pulsating tools.
Otras especificaciones a petición.

Descripción

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Artículo

Denominación	Roscas interiores	Conexión	Longitud (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24