

# LKM MM ST DK

Manguito de acoplamiento insertable (aire) con seguro

**HANSA FLEX**

## Características

<b>Construcción</b>	Manguito para acoplamiento de cierre rápido
<b>Conexión 1</b>	Conexión de tubo flexible
<b>Conexión 2</b>	
<b>Presión de servicio</b>	máx. 12 bares
<b>Flujo de aire</b>	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Temper. de medios</b>	-20 °C to +70 °C
<b>Carcasa</b>	Aluminium, anodised
<b>Rosca</b>	Nickel-plated brass
<b>Piezas int.</b>	Stainless steel
<b>Botón, válv.</b>	Hardened, galvanised steel
<b>Material obturador</b>	NBR



## Nota

Not suitable for hitting / pulsating tools.  
Otras especificaciones a petición.

## Descripción

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Artículo

Denominación	para diámetro interno tubo flexible (mm)	Conexión	Longitud (mm)	SW (mm)
LKM 06 MM ST DK	6	Stem, I.D. 6	88,5	21
LKM 09 MM ST DK	9	Stem, I.D. 9	88,5	21
LKM 13 MM ST DK	13	Stem, I.D. 13	88,5	21