

PHD 200 VA

Kaetud vooliku pressühendus

HANSA FLEX

Omadused

Ühendusetüüp	Hülssühendus
sobilik	4SP (HD 400 ab DN 10) 2SN (HD 200, HD 200T, HD 200RM, HF 200, HW 200)
Materjal	Roostevaba teras



Vihje

Ühenduse paigutus sõltub voolikutüübist.

PHD406VA ainult 4SP DN06 jaoks

Artikkel

Märgistus	DN*	Suurus	Toll	D1 (mm)	D3 (mm)	LF (mm)
PHD 206 VA	6	4	1/4"	22,0	10,4	34,5
PHD 406 VA	6	4	1/4"	22,0	10,4	34,5
PHD 208 VA	8	5	5/16"	24,0	12,0	34,5
PHD 210 VA	10	6	3/8"	26,0	14,0	35,0
PHD 213 VA	12	8	1/2"	30,0	17,3	37,0
PHD 216 VA	16	10	5/8"	33,0	20,2	40,0
PHD 220 VA	19	12	3/4"	38,0	24,3	45,0
PHD 225 VA	25	16	1"	46,0	31,5	50,0
PHD 232 VA	31	20	1.1/4"	58,0	37,8	70,0
PHD 240 VA	38	24	1.1/2"	64,2	44,9	70,0
PHD 250 VA	51	32	2"	76,0	57,5	80,0

DN = nimiläbimõõt, nimilaius