

# PA 500 AJ 90 VA

Pressarmatuur, DKJ W90°

**HANSA FLEX**

## Omadused

Rakendusvaldkond Pressarmatuur HD 500 voolikutele

Ühendus 1 UN/UNF-mutrikeere

Tihenditüüp 1 74° sisekoonus


Lühend DKJ

Tavaline ISO 8434-2

Integreerimine rebenemiskaitsega (Interlock)

Komplektis Nippelotsik + pressühendus

Materjal Roostevaba teras



## Artikkel

Märgistus	DN	Suurus	Toll	G1	L2 (mm)	S1
PA 520 AJ 90 VA	19	12	3/4"	1.1/16" -12 UN	72,0	32
PA 520 AJ 25 90 VA	19	12	3/4"	1.5/16" -12 UN	79,0	41
PA 525 AJ 90 VA	25	16	1"	1.5/16" -12 UN	86,0	41
PA 525 AJ 32 90 VA	25	16	1"	1.5/8" -12 UN	93,0	50
PA 532 AJ 90 VA	31	20	1.1/4"	1.5/8" -12 UN	96,0	50
PA 532 AJ 40 90 VA	31	20	1.1/4"	1.7/8" -12 UN	98,0	60
PA 540 AJ 90 VA	38	24	1.1/2"	1.7/8" -12 UN	107,0	60
PA 540 AJ 50 90 VA	38	24	1.1/2"	2.1/2" -12 UN	-	-
PA 550 AJ 90 VA	51	32	2"	2.1/2" -12 UN	151,5	70