

Omadused

Ühendus 1 BSP-väliskeere, silindriline

Ühendus 2 Voolikühendus

Materjal Messing



Artikkel

| Märgistus | Ühendusniit | Vooliku-ID jaoks (mm) | SW (mm) | Töörõhk bar |
|-----------|------------------|--------------------------|------------|-------------|
| T 184 M | G 1/8" -28 | 4 | 14 | PN 16 |
| T 186 M | G 1/8" -28 | 6 | 14 | PN 16 |
| T 189 M | G 1/8" -28 | 9 | 14 | PN 16 |
| T 144 M | G 1/4 tolli - 19 | 4 | 17 | PN 16 |
| T 146 M | G 1/4 tolli - 19 | 6 | 17 | PN 16 |
| T 149 M | G 1/4 tolli - 19 | 9 | 17 | PN 16 |
| T 1413 M | G 1/4 tolli - 19 | 13 | 17 | PN 16 |
| T 386 M | G 3/8" -19 | 6 | 19 | PN 16 |
| T 389 M | G 3/8" -19 | 9 | 19 | PN 16 |
| T 3813 M | G 3/8" -19 | 13 | 19 | PN 16 |
| T 126 M | G 1/2" -14 | 6 | 24 | PN 16 |
| T 129 M | G 1/2" -14 | 9 | 24 | PN 16 |
| T 1213 M | G 1/2" -14 | 13 | 24 | PN 16 |
| T 1219 M | G 1/2" -14 | 19 | 24 | PN 16 |
| T 349 M | G 3/4" -14 | 9 | 27 | PN 16 |
| T 3413 M | G 3/4" -14 | 13 | 32 | PN 16 |
| T 3419 M | G 3/4" -14 | 19 | 32 | PN 16 |
| T 1019 M | G 1" -11 | 19 | 26 | PN 16 |
| T 1025 M | G 1" -11 | 25 | 38 | PN 16 |

SW = võtme suurus