

HK CFB

Õlisisselaskega liigendsilindri põhi

HANSA FLEX

Omadused

Materjal Teras S355J0 (Fe510C)



Artikkel

| Märgistus | Ø AL (mm) | Ø F (mm) | Ø T (mm) | C (mm) | G | H (mm) | I (mm) | S (mm) | Z (mm) | Kaal (kg) |
|------------------|--------------|-------------|-------------|-----------|--------|-----------|-----------|-----------|-----------|--------------|
| HK CFB 040 050 4 | 40 | 16,20 | 50 | 24,8 | G 1/4" | 19,0 | 39,0 | 2,00 | 46 | 0,56 |
| HK CFB 050 060 6 | 50 | 20,25 | 60 | 24,8 | G 3/8" | 31,0 | 56,0 | 2,00 | 51 | 0,84 |
| HK CFB 060 070 6 | 60 | 25,25 | 70 | 24,8 | G 3/8" | 33,0 | 63,0 | 2,00 | 57 | 1,15 |
| HK CFB 061 071 6 | 60 | 25,25 | 70 | 25,0 | G 3/8" | 29,5 | 48,0 | 2,00 | 47 | 0,81 |
| HK CFB 070 080 6 | 70 | 25,25 | 80 | 39,5 | G 3/8" | 42,0 | 82,0 | 2,00 | 65 | 2,70 |